

aprilia®

SR
hp.e



HANDLEBAR

Distinct, Sporty Handlebar with integrated turn indicator lights with carbon finished rear cover

SEAT

Wide Cushioned Dual Cut Seat

SUSPENSION

Enhanced comfort with single arm adjustable rear suspension (175cc). In 125cc, the adjustable suspension is not available

EXHAUST

Racing inspired exhaust note with stylised carbon finish

125/175CC ENGINE

Powerful hp.e Engine

TRANSMISSION

CVT for smooth ride and quick acceleration

LARGE WHEELS & WIDER TYERS

14" Wheels with 5 spoke alloy wheels for confident riding on any terrain



INSTRUMENT CLUSTER

5.5 inch TFT display

LIGHT UNIT

LED head lamp for wider spread and visibility

SUSPENSION

Telescopic fork front suspension for superior handling

CALIPER

Sporty looking twin piston floating caliper

DISC BRAKE

220 mm ventilated front disc brake
ABS in 175cc and hydraulic CBS in 125cc

SR175



SR-**G**P

REPLICA



TRIBUTE





LIFESTYLE CLOTHING

DISCOVER THE ENTIRE COLLECTION
AT **YOUR NEAREST DEALERSHIP.**

A person wearing a racing helmet and a red and black racing suit, standing in front of a blue corrugated metal wall. The helmet is black with a clear visor and features the word 'Aprilia' in white and red. The suit is red and black with the 'Aprilia' logo on the chest and a white star logo on the sleeve.

HELMETS AND TECHNICAL CLOTHING

DISCOVER THE ENTIRE RANGE OF HELMETS
AND TECHNICAL CLOTHING
AT **YOUR NEAREST DEALERSHIP.**

SR 175 hp.e



**MATTE
PRISMATIC
DARK**



**GLOSSY
TECH
WHITE**



GP REPLICA



TRIBUTE

SR 125 hp.e



**GLOSSY
MAZDA GREY +
MATTE BLACK**



**GLOSSY
RED +
MATTE BLACK**



**MATTE
BLACK**



TRIBUTE

COLOUR RANGE

***For more information
visit apriliaindia.com***

	SR 175 hp.e / GP REPLICA / TRIBUTE	SR 125 hp.e / TRIBUTE
ENGINE		
Type	Single cylinder, 4 stroke, SOHC 3 valve	Single cylinder, 4 stroke, SOHC 3 valve
Cylinder Bore	60.6 mm	52 mm
Stroke	60.6 mm	58.6 mm
Piston Displacement	174.7 cm³	124.45 cm³
Compression Ratio	9.5:1	10:1
Fuel Pump	KEIHIN	KEIHIN
Power Supply	Electronic injection with throttle body, Single injector	Electronic injection with throttle body, Single injector
Air Filter	Paper Type	Paper Type
Lubrication System	Forced feed circulation, wet sump	Forced feed circulation, wet sump
Maximum Power	9.76 kW @7200 RPM	7.8 kW @7400 RPM
Maximum Torque in Nm	14.14 Nm @ 6000 RPM at crankshaft	10.4 Nm @ 6200 RPM at crankshaft
Maximum Speed	95 km/hr	90 km/hr
Engine Idling RPM	1800±100	1800±100
Starting System	Electric Starter	Electric Starter
Fuel	E20 Compliant	E20 Compliant
TRANSMISSION		
Clutch	Self Ventilating Dry Centrifugal Clutch	Self Ventilating Dry Centrifugal Clutch
Transmission	Auto Expendable - CVT with forced circulation air cooling	Auto Expendable - CVT with forced circulation air cooling
Primary Reduction	0.802:1 - 2.801:1	0.802:1 - 2.801:1
Final Reduction	9:48 : 1	11.73 : 1

WARRANTY

- 5 YEARS

Manufacturer's warranty (60,000 kms*)
- 1 YEAR

4 free services (*kms range defined in Owner's manual)
- 2 YEARS

Road-Side Assistance with no extra cost.

- Coverage of repair costs for faults due to manufacturing or assembly defects of parts.
- Replacement of any damaged parts with OE spare parts, labour included.
- Roadside assistance including towing service.
- Specialized service assistance by Piaggio's authorized dealers.

The company reserves the right to make technical and aesthetic changes at any time. Full information on models and accessories is available at www.aprilia.com. Ride carefully, always wearing a helmet and suitable gear. Always comply with the rules of the road and respect the environment. Read the operating and maintenance manual carefully. Always ask for original and approved spare parts in accordance with current legislation. Visit an Official Aprilia Dealership or Authorised Retailer for a secure purchase and guaranteed service support.

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV
= ISO 14001 =

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001 =

COMPANY WITH
SAFETY SYSTEM
CERTIFIED BY DNV
= OHSAS 18001 =

Aprilia is a registered trademark of Piaggio & C. S.p.A.

*According to regulation (EU) No 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume.



apriliaindia.com